



Material Safety Data Sheet September 08, 2016

69011-18-3 (20-50%)

7732-18-5 (40-70%)

Synonyms: Mixed Bed ion exchange resin CAS Number: 69011-20-7 (10-30%)

Address: 3345 Stop 8 Rd, Dayton Ohio, 45414, USA

Website: www.AMERIWATER.com

Section 01: Chemical Product Identification

Domestic Trade Name: **45 BATCH MIXED BED RESIN** Export Trade Name: 45 BATCH MIXED BED RESIN **Product Use**: All applications where deionized water is needed.

Manufacturer/Supplier: AmeriWater, LLC General Information: 937-461-8833

Section 02: Hazards Identification:

| GHS Classification: | | | | | |
|--|------------------------------------|------------------------------|--|--|--|
| Health | Environmental | Physical | | | |
| Health Hazards: | Acute Toxicity: | Boiling Point: N/A | | | |
| Primary Route of Exposure: Skin contact | Mutagenicity: No Data | Melting/Freezing Point: | | | |
| Inhalation: Inhalation of dust can cause | Oral Toxicity: No Data | Approximately 0°C – 32°F | | | |
| irritation of nose, throat, and lungs. | Skin Irritation: Causes | Appearance: Yellow to | | | |
| Skin Contact: Exposure to skin may cause | slight irritation | Brown Beads | | | |
| slight irritation, but immediate first aid not | Inhalation Toxicity: Inhalation of | Specific Gravity: 1.1 g/ml | | | |
| likely required | dust can cause irritation of nose, | Odor: Slight Amine | | | |
| Eye contact: Material can cause corrosion to | throat, and lungs | Vapor Pressure: 17 mm Hg | | | |
| eyes, reddening, tearing. May cause | Chronic Exposure: No Data | Vapor Density: 0.62 | | | |
| permanent eye damage. | Available | Water Solubility: Negligible | | | |
| Ingestion: Material is not harmful if | Eye Contact: can cause corrosion | | | | |
| accidentally ingested | to eyes, reddening, tearing. May | | | | |
| Medical Conditions Aggravated by | cause permanent eye damage. | | | | |
| <i>Exposure:</i> May aggravate existing skin ailments. | Sensitizer: Not a sensitizer | | | | |

GHS Label:

Symbols:

Hazard Statements WARNING H315: Causes skin irritation (Category 2) H319: Causes serious eye irritation (Category 2A)

Precautionary Statements

P264: Wash hands thoroughly after handling. P280: Wear protective gloves/protective clothing/eye

protection/face protection

P284: In case of inadequate ventilation wear respiratory protection.

P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing.

P333+313: If skin irritation or a rash occurs: Get medical advice/attention.

P337+313: If eye irritation persists get medical advice/attention.

P403+233: Store in a well-ventilated place. Keep container tightly closed.

P411: Store at temperatures not exceeding 50 °C/ 122 °F.

Section 03: Composition / Information on Ingredients

Component Polystyrene sulfonate in the hydrogen form

Trimethylamine functionalized chloromethylated copolymer of polystyrene in the hydroxide form

Water

Section 04: First Aid Measures

Eye: Wash immediately with water-seek attention if discomfort continues.

Skin: Wash with soap and water- seek medical attention if a rash develops.

Inhalation: No adverse effects expected. Normal use of product does not produce odors or vapors.

Ingestion: No adverse effects expected for small amounts, larger amounts can cause stomach irritation. Seek medical attention if discomfort occurs.

Section 05: Fire Fighting Measures

Suitable Extinguishing Media: Water, CO2, foam, dry powder.

Fire Fighting Procedures: Follow general fire fighting procedures indicated in the work place. Seek medical attention if discomfort continues.

Unusual Fire and Explosion Hazards: None known

Combustion Products: Carbon oxides and other toxic gasses and vapors.

Autoignition Temp: N/A Flammable Limits: LEL (Lower Explosive Limits) N/A

Section 06: Accidental Release Measures

Personal Precautions: Keep people away, spilled resin can be a slipping hazard, wear gloves and safety glasses to minimize skin or eye contact.

Incompatible Chemicals: Strong oxidants can create risk of combustion products similar to burning, exposure to strong bases can cause a rapid temperature increase.

Environmental Precautions: Keep out of public sewers and waterways.

Containment Materials: Use plastic or paper containers, unlined metal containers not recommended. **Methods of Clean-up:** Sweep up material and transfer to containers

Section 07: Handling and Storage

Handling: Avoid prolonged skin contact. Avoid contact with salts or with salty water to prevent premature exhaustion of the resin. Keep resin moist and avoid allowing resin to completely dry.

Storage: Store in a cool dry place (0° to 45° C) in the original shipping container. This product is thermally sensitive and will have reduced shelf life if subjected to extended periods of time at temperatures exceeding 45° C. Although freezing does not usually damage ion exchange resins, avoid repeated freeze thaw cycles.

TSCA considerations: Ion exchange resins should be listed on the TSCA Inventory in compliance with State and Federal Regulations.

Section 08: Exposure Control/Personal Protection

OSHA exposure limits: None noted.

Engineering Controls: Provide adequate ventilation.

Personal Protection Measures:

Eye Protection Safety glasses or goggles. *Respiratory Protection* Not required for normal use. *Protective Gloves* Not required for limited exposure but recommended for extended contact.

CAS Number

69011-20-7 (10 - 30%)

69011-18-3 (20 - 50%)

7732-18-5 (40 – 70%)

Section 09: Physical and Chemical Properties

Appearance: Solid beads approx 0.6 mm diameter Flammability/explosive limits: Flammable above 500° C Odor: None Physical State: Solid Vapor pressure: Not available Odor threshold: Not available Vapor density: Not available pH: Acidic or basic when mixed with water Relative density: Approx 700 grams/Liter

Melting point/freezing point: Does not melt, freezes at approx. 0 ° C Solubility: Insoluble in water and most solvents Boiling point: Does not boil Flash point: Approx 500° C Evaporation rate: Does not evaporate Partition Coefficient (n-octonol/water): Not applicable Auto-ignition temperature: Approx 500° C Decomposition temperature: Above 230° C Viscosity: Not applicable

Section 10: Stability and Reactivity

Stability: Stable under normal conditions.

Conditions to Avoid: Heat, exposure to strong oxidants.

Hazardous by-products: Organic sulfonates, amines, charred polystyrene, aromatic acids and hydrocarbons, organic amines, nitrogen oxides, carbon oxides, chlorinated hydrocarbons,

Incompatible materials: Strong oxidizing agents (such as HNO₃), strong bases (such as NaOH), strong acids (such as HCI and H₂SO₄)

Hazardous Polymerization: Does not occur

Section 11: Toxicological Information

Likely Routes of Exposure: Oral, skin or eye contact. Effects of exposure: Delayed None known. Immediate (acute) Rash or burn caused by acidity or causticity. Chronic None known. **Toxicity Measures** Skin Adsorption Unlikely Ingestion Oral toxicity believed to be low but no LD50 has been established. Inhalation Unknown, vapors are very unlikely due to physical properties (insoluble solid). **Toxicity Symptoms** Skin Adsorption Rash or burn. Ingestion Indigestion or general malaise. Inhalation Unknown.

Carcinogenicity: None knownskin.

Section 12: Ecological Information

| Eco toxicity | Not harmful to plant or animal life. |
|-----------------------|---|
| Mobility | Insoluble, acidity or causticity may escape if wet. |
| Biodegradability | Not biodegradable. |
| Bioaccumulation | Insignificant. |
| Other adverse effects | Not Harmful to the environment. |

Section 13: Disposal Considerations

| General considerations | Material is non-hazardous. |
|------------------------------|---|
| Disposal Containers | Most plastic and paper containers are suitable. Avoid use of unlined metal |
| | containers. |
| Disposal methods | No specific method necessary. |
| Sewage Disposal | Not recommended. |
| Precautions for incineration | May release acids and toxic vapors when burned. |
| Precautions for landfills | pH of spent resin may be high or low. Resins used to remove hazardous materials |
| | may then become hazardous mixtures. |

Section 14: Transport Information

Transportation ClassNot classified as a dangerous good for transport by land, sea, or air.TDGNot regulated.IATANot regulated.DOT (49 CFR 172.101)Not Regulated.

Section 15: Regulatory Information

| CERCLA | Not regulated |
|----------------------|--------------------------|
| SARA Title III | Not regulated |
| Clean Air act | Not regulated |
| Clean Water Act | Not regulated |
| TSCA | Not regulated |
| Canadian Regulations | |
| WHMIS | Not a controlled product |
| TDG | Not regulated |
| Mexican Regulations | Not Dangerous |
| | |

Section 16: Other Information

National Fire Protection Association (NFPA) Ratings: This information is intended solely for the use of individuals trained in the NFPA system.

| | Health: Flammabil Reactivity: Special: | | | |
|-----------------------|---|--------------|----------|-------------|
| Scale: 0 = Negligible | 1 = Slight | 2 = Moderate | 3 = High | 4 = Extreme |

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features. Regulatory requirements are subject to change and may differ from one location to another. It is the buyer's responsibility to ensure that their activities comply with federal, state, and local laws.