NPE STANDARD REPAIR PARTS LIST

item No.	Description	Materials of Construction	
100	Casing	AISI 316L Stainless Steel	
101	Impeller		
108A	Motor adapter with foot		
108B	Motor adapter less foot		
108C	Motor adapter with foot and Flush		
108D	Motor adapter less foot with Flush		
123	Deflector	BUNA-N	
184A	Seal housing std.	AISI 316L S.S.	
184B	Seal housing with seal flush		
240	Motor support	300 S.S.	
240	Rubber channel	Rubber	
304	Impeller locknut	AISI 316 S.S.	
347	Guidevane	AISI 316L S.S.	
	Seal-Ring, guidevane	Vîton (standard)	
349		EPR	
i		BUNA	
370	Socket head screw, casing	AISI 410 S.S.	
371	Bolts, motor	Steel/plated	
383	Mechanical seal		
408	Drain and vent plug, casing	AISI 316 S.S.	
	O-Ring, drain plugs	Viton (standard)	
412B		EPR	
		BUNA	
	O-Ring, casing	Viton (standard)	
513		EPR	
	-	BUNA	

MECHANICAL SEAL APPLICATION CHART

ltem 383 Mechanical Seal (⅓" seal)					
Rotary	Stationary	Elastomers	Metal Parts	Part No.	
Carbon	Sil-Carbide	EPR	31655	10K18	
Carbon		. Viton		10K55	
Eil Cashida		EPR		10K81	
Sil-Carbide		Viton		10K62	

NOTE: Close coupled units supplied with $\frac{1}{2}$ HP 1750 RPM, $\frac{1}{2}$ - 3 HP Explosion Proof or 5 HP motors, utilize motor adapter less foot and a footed motor.

NOTE: Frame mounted units (NPE-F) utilize the XS Power frame and motor adapter less foot. For repair parts for the power frame refer to the XS-Power frame repair parts page in the parts section of your catalog. To order the power frame complete order item 14L61

